

POLAR WHITE

Version
Island 35 cm - White - 800 m3/h

Collection
Design

EAN code
8034122342139



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

- Painted white steel
- Electronic control
- LED lighting
- Metallic grease filter, removable and washable
- Charcoal filter

OPTIONAL ACCESSORIES

103050091
Round charcoal filter Ø170 mm - Type 6

TECHNICAL FEATURES

- Installation type**
Island
- Dimensions**
35 cm
- Finishing**
Painted white steel
- Motor**
800 m³/h
- Type of control**
Electronic control
- Speed**
3 + boost
- Lighting**
Led 3x1,2 W - 3200 K
- Filter**
Metallic filter "Base" - 235x245 mm (White)
- Charcoal filter**
Round charcoal filter Ø170 mm - Type 6 (optional)
- Minimum distance**
Gas hob: 60 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES


- Gross weight**
25 kg
- Net weight**
21 kg
- Volumes**
0.3 m³
- Packaging size**
Length
995 mm
Height
500 mm
Depth
595 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
280 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- Plug type**
Shuko

MOTOR TECHNICAL SHEET

- Maximum capacity**
710 m³/h
I.E.C. 61591
- Maximum noise level**
67 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
500 Pa
- Max. motor power**
215 W
- ENERGY CLASS**
B



POLAR WHITE

Version
Island 35 cm - White - 800
m3/h


Collection
Design

EAN code
8034122342139

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	48	54	61	67
Capacity (m3/h) I.E.C.61591	290	380	490	710
Maximum pressure (Pa)	400	450	480	500
Power (W)	134	156	180	215
Air outlet	150	150	150	150

CAPACITY / PRESSURE




POLAR WHITE

Version
Island 35 cm - White - 800 m3/h

Collection
Design

EAN code
8034122342139

ENERGY LABEL



PF		
S	Falmec Spa	
M	Island 35 cm - White - 800 m3/h	
AEC	61,4	kWh/a
EEC	B	
FDE	28,1	
FDEC	A	
LE	24,2	
LEC	B	
GFE	76,0	
GFEC	C	
Qmin	290,0	m³/h
Qmax	490,0	m³/h
Qboost	710,0	m³/h
SPEmin	48	dBa
SPEmax	61	dBa
SPEboost	67	dBa
PO	-	W
PS	0,48	W
PI		
F	1	
EEl	59,6	
Qbep	371,0	m³/h
Pbep	412	Pa
Qboost	710,0	m³/h
Wbep	151,0	W
WL	8,60	W
Emiddle	208	lux
Lwa-SPEmax	61	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEl_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.