

Version	Wall - 120 cm - Inox - 950 m3/h
Design	Falmec Lab
Collection	Professional
TECHNICAL FEATURES	
Materials/Finishes	Scotch brite stainless steel (AISI 304)
Features	Professional Buffle filters with liquid collector
Control	Electronic control
Function	Extracting
Chimney	Possible to duct wall mounted from rear
Lighting	Dynamic Light (2700K - 5600K)
	Dimmable lighting
	LED 4x1,2 W - 2700 K / 5600 K
Filters	Professional Baffle Filters
Dimensions	120 cm
Minimum Electric hob distance	52 cm
Minimum Gas hob distance	63 cm
Notes	From 04.11.2024 the dynamic and dimmable light is included.



Photograph is for information purposes only. May not correspond to the selected version

CONNECTION AND CONSUMPTION FUNCTIONS



Maximum consumption	320 W
Voltage/Frequency	220-240V 50-60Hz
Plug	Shuko

MOTOR


Motor	950 m³/h
Maximum capacity	860 m³/h I.E.C.61591
Maximum sound level	64 dB (A)re1pW I.E.C. 60704-2-13
Energy class	B

WEIGHTS AND VOLUMES

Gross weight	36 kg
Net weight	31 kg
Volume	0.48 m3
Packaging dimensions	L 1310 x H 622 x P 595 mm



Rear view



Optional chimney


Optional accessories


Code	Description
KCQAN.00#I	Chimney - Inox
KACL.815	Protective cleaning cloths for stainless steel (box 10 pcs)

ENGINE SPECIFICATIONS

Motor speed	1	2	3	4
Noise dB(A) re1pW I.E.C. 60704-2-13	53	58	64	69
Capacity	350	470	620	860
Maximum pressure (Pa)	500	540	560	600
Motor power (W)	185	215	240	260
Air outlet	150	150	150	150

FLOW RATE / PRESSURE





PF		
S	Falmecc Lab	
M	Wall - 120 cm - Inox - 950 m3/h	
AEC	70.3	kWh/a
EEC	B	
FDE	29.3	
FDEC	A	
LE	31.4	
LEC	A	
GFE	74	
GFEC	C	
Qmin	350	m³ /h
Qmax	620	m³ /h
Qboost	860	m³ /h
SPEmin	53	dBa
SPEmax	64	dBa
SPEboost	69	dBa
PO	0	W
PS	0.48	W
PI		
F	0.9	
EEL	55.2	
Qbep	473	m³ /h
Pbep	435	Pa
Qboost	860	m³ /h
Wbep	195	W
WL	8.6	W
Emiddle	270	lux
Lwa-SPEmax	64	dBa

PF_Scheda prodotto conforme a 65/2014 S_Vendor name / M_Project identification / AEC_Yearly energy consumption (AEC) hood / EEC_Energy efficiency class / FDE_Fluid dynamic efficiency (FDE) hood / FDEC_Fluid dynamic efficiency class / LE_Light efficiency (LE) hood / LEC_Light efficiency class of luminous efficiency / GFE_Fat filtration efficiency / GFEC_Fat filtration efficiency class / Qmin_Airflow (in m³/h) at minimum power under normal use conditions / Qmax_Airflow (in m³/h) at maximum power under normal use conditions / Qboost_Airflow (in m³/h) at the intensive power / SPEmin_A-weighted sound power of airborne noise emissions at the minimum power under normal use conditions / SPEmax_A-weighted sound power of airborne noise emissions at the maximum power under normal use conditions / SPEboost_A-weighted sound power of airborne noise emissions under intensive or boost use conditions / PO_CPower consumption in off mode (Po) / Ps_CPower consumption in standby mode (Ps).

PI_Additional information in accordance with 66/2014 4 F_Fattore di incremento nel tempo / EEL_Indice di efficienza energetica / Qbep_Velocità del flusso d'aria misurato nel punto di efficienza migliore / Pbep_Pressione dell'aria misurata nel punto di efficienza migliore / Qboost_Flusso d'aria massimo / Wbep_Ingresso energia elettrica misurato nel punto di efficienza migliore / WL_Potenza nominale del sistema luminoso / Emiddle_Illuminazione media del sistema luminoso sulla superficie di cottura / Lwa=SPEmax_Livello di pressione sonora alla potenza massima.