

EN PURSU2 / PURSU2R product information sheet

High-gloss glass ceramic:



PURSU2

S Pure combined induction cooktop with integrated cooktop extractor – recirculation

Matt glass ceramic:



PURSU2R

S Pure Rough combined induction cooktop with integrated cooktop extractor – recirculation

General product information:

Product:	Induction cooktop and cooktop extractor in a single appliance
Product highlights:	Induction cooking zones on the left, surface induction cooking zones on the right, intuitive touch controls, BORA Assist for simpler cooking experiences, wider range of functions with the BORA JOY app, filter change from above through the air inlet opening
Model:	Recirculation system with integrated odour filter
Minimum installation dimensions:	Kitchen unit with a min. width of 60 cm
Safety and warning information:	See operating and installation instructions

PISPURSU2EN-10001

PURSU2 / PURSU2R

S Pure combined induction cooktop with integrated cooktop extractor – recirculation

Technical data

Multiphase supply voltage	380–415 V 2N/3N
Single-phase supply voltage	220–240 V
Frequency	50–60 Hz
Maximum power consumption	7360 W (4400 W / 3600 W)
3-phase fuse protection/power supply	3 × 16 A
2-phase fuse protection/power supply	2 × 16 A
1-phase fuse protection/power supply	1 × 32 A (1 × 20 A / 1 × 16 A)
Dimensions (width × depth × height)	580 × 515 × 199 mm
Weight (incl. accessories / packaging)	20.2 kg
Surface material	Glass ceramic
Cooktop extractor / cooktop power levels	1–9, P
Size of front left cooking zone	Ø 95 mm
Size of rear left cooking zone	Ø 140 mm
Size of right cooking zones	230 × 230 mm
Front left cooking zone output	400 W
Rear left cooking zone output	900 W
Right cooking zone output	2100 W
Front left cooking zone output on power setting	600 W
Rear left cooking zone output on power setting	1350 W
Output of right cooking zones on power setting	3000 W
Filter material	Activated charcoal with ion exchanger
Maximum filter service life	150 hrs (1 year)
Guaranteed availability period for software updates (from product discontinuation date)	5 years

Product description

- Connectivity and BORA Assist
- Intuitive tricolour sControl+ operating panel
- Oversized surface induction cooking zones (right)
- Ultra-compact design
- Stainless steel grease filter
- Integrated grease drip tray
- Activated charcoal filter for effective odour elimination
- eSwap – easy filter changes

Functions

BORA Assist function Fry, coffee function, power setting, automatic extractor function, automatic after-run, filter status and filter service display, pan size recognition, automatic heat-up function, heat retention function, bridging function (right), cooking zone timer, pause function, short-time timer

Safety features

Child lock, control lock, cleaning lock, residual heat indicator, safety shut-down, overheating protection

Scope of delivery

Induction cooktop with integrated cooktop extractor – recirculation PURSU2/PURSU2R, air inlet nozzle PUED2, stainless steel grease filter, odour filter GFESP, operating and installation instructions, installation template, installation accessories

Accessories

Odour filter GFES/GFESP, stainless steel grease filter PUEF, air inlet nozzles PUED2 and PUXED2, sealing tape UDB25, cooktop frame KFR580AB, side frame USL515/USL515AB, grill pan for surface induction KWGPFI

Product and planning information

- The mains supply cable is to be provided on site
- Front power socket
- Flush installation or surface mounting possible
- Sufficient ventilation below the cooktop must be ensured
- The drawers or shelves in the base unit must be removable (for maintenance and cleaning)
- Air purification box fitted with a telescopic extension (extendible up to 80 mm) for connection to the back of the kitchen unit
- Suitable for use with all BORA sockets
- Cannot be installed above an oven
- When installation is complete, the appliance is to be sealed in using heat-resistant silicone sealant

